

ILC 96 & Milk Fridge



DIMENSIONS
W = 303mm x D:511mm x H:
582mm

FEATURES

ILC 96

- 7th LCD touch screen. Android system, more functional applications available
- 20+ programmable beverages can be customised
- Programmable video for brand promotion and advertisements
- Large 100g bean hopper
- Tap water connection and 6L water tank
- Multiple cups for conference occasions
- Coffee and milk/foam can be made simultaneously for high efficiency
- Optional drainage pipe and auto slag-failing system

MILK FRIDGE

- Air cooling system with fin type evaporator, auto defrost
- Electronic thermostat with 0-4°C temperature display
- Integrated black powder coated foam door, easy to clean
- Pre-drilled milk line holes on both sides
- 5 Blister white ABS inner liner and 4 adjustable feet

SPECIFICATIONS

ILC 96

- Voltage/Frequency: 220 - 240V / 50-60Hz
- Variable brewing chamber: 8-14g
- Heating power: 2700W
- Pre-brew system
- No. of thermoblock heating systems: 2
- No of pumps: 2
- Pump pressure: 19 Bar
- Bean container capacity: 1000g
- Capacity of coffee ground: 30-35 portions
- Capacity of waste water: 2L
- Length of power cord: 1.8m
- Height of coffee spout: 100mm-160mm
- N.W/G.W: 17/21kg
- Dimensions (D"W"H): 511 x 303 x 582mm
- Optional IoT and payment system
- Power Requirement: 15AMP

MILK FRIDGE

- Rated power: 61W
- Voltage/Frequency: 220-240V 50/60Hz
- Rated current: 0.5A
- Certification Standard: CE
- Forced air cooling: ≤ 8h
- Temperature range: 0-4°C under class 3
- Refrigerant /Amount: R600a/12g
- Inner capacity: 6L
- Milk Hose Hole Size: Dia. 7mm
- Noise: ≤ 45dB

Designed and manufactured under license in Italy

Essential Coffee

Specialty Coffee Roasters

AU



sales@essentialcoffee.com.au



1300 324 111

NZ



info@essentialcoffee.co.nz



0800 324 111